

Container facilities – RESTROOM MODEL LINE

20' Container Restroom

General Features:

Enclosure: 20' Container
 Approx. Shipping Weight: 8,800 lbs.
 Approx. Footprint: 20'-0" X 8'-0"
 Approx. Overall Dims: 20-10" X 9'-2" X 8'-6"

Lifting Methods:

Bottom Corner Blocks: Yes
 Top Corner Blocks: Yes
 Forklift: Yes
 Other: Yes (Overhead crane w/lifting lugs)

Electrical Data:

Load Center Main Amps: 100
 Voltage & Frequency: 240/60Hz/single phase
 Demand KVA & Amps: 22/100

Interior/Exterior Specs:

Wall/Ceiling Insulation: R-14
 Entry Door/Window: 5-door (counting utility & service doors)/0
 Mechanical Room (LXW): 5' X 7'-6"
 Private Deluxe Stall*: 2 (*Components: toilet, sink, towel dispenser, sanitary napkin supply/disposal bins, purse/cargo hanger, mirror, LED light, trash bin (55- gallon), deadbolt with occupancy display)
 Private Stall: 2
 Common Wash Station: 1 (sink/towel dispenser/mirror/trash bin (55-gallon))
 Rugged entry stair set: 4
 Water heater 1 (18-gallon/240V/3800watts)

Heating/Cooling Specs:

Cooling Capacity/BTUH: 18,000 (ducted, forced air system with 17,000 BTU electric supplement coil)

Optional Features:

Low fill-water alert
 Interface with security system
 Security cameras

Suggested Site Attributes:

- level ground, with good drainage and free of debris
- no overhead obstructions (that could hinder delivery or pickup)
- concrete slab (ideal, but not necessary)
- gravel bed (ideal, but not necessary, adds drainage and stability)
- support blocks & ground locks should be used after installation

Transport:

Lifting capacity of 10,000#

