

Container facilities – RESTROOM MODEL LINE

40'-0" Container Restroom – OPEN FLOOR PLAN (2 Private Stalls/4 Open Stalls/3 Urinals)

General Features:

Enclosure:	40'-0" Container
Approx. Shipping Weight:	12,500 lbs.
Approx. Footprint:	40'-0" X 8'-0"
Approx. Overall Dims:	40'-0" X 9'-2" X 8'-6"

Lifting Methods:

Bottom Corner Blocks:	Yes
Top Corner Blocks:	Yes
Forklift:	Yes
Other:	Yes (Overhead crane w/lifting lugs)

Electrical Data:

Load Center Main Amps:	100
Voltage & Frequency:	240/60Hz/single phase
Demand KVA & Amps:	22/100

Interior/Exterior Specs:

Wall/Ceiling Insulation:	R-14
Entry Door:	4
Mechanical Room (LXW):	5' X 7'-6"
Private Deluxe Stall*:	2 (*Components: toilet, sink, towel dispenser, sanitary napkin supply/disposal bins, purse/cargo hanger, mirror, LED light, trash bin (55- gallon), deadbolt with occupancy display)
Standard Stall:	4
Common Wash Station:	2 (sink/towel dispenser/mirror/trash bin)
Urinal:	3
Rugged entry stair set:	3
Water Fill tank	1 (500-gallon)
Water heater	1 (18-gallon/240V/3800watts)
Gray tank	1 (1350-gallon)

Optional Features:

Low fill-water alert
Interface with security system
Security cameras

Suggested Site Attributes:

- level ground, with good drainage and free of debris
- no overhead obstructions (that could hinder delivery or pickup)
- concrete slab (ideal, but not necessary)
- gravel bed (ideal, but not necessary, adds drainage and stability)
- support blocks & ground locks should be used after installation

Transport:

Lifting capacity of 12,500#

PRODUCT
IMAGE
UNAVAILABLE

Item No. 86-00010-00